

WE CLAIM AS OUR INVENTION:

1. An invention for generating a security imprint comprising:
- a security module containing a first program memory in which a first program is stored and a security module data processing unit connected to said first program memory and being programmed by said first program to calculate a multi-byte security code from existing system data and to be able to receive new system data to modify said existing system data;
- a separate data processing unit disposed externally of said security module and having a second program memory in which a second program is stored, said separate data processing unit being programmed by said second program to edit print data to compile a print image that contains said security code as a security imprint and that embodies a monetary value for franking a mail item; and
- said security module data processing unit being further programmed by said first program to, immediately upon receipt of said new system data, validate said new system data and determine whether said new system data are required for said security code and, if so, to immediately begin recalculating said security code in a first routine and, in a second routine, to finish recalculating said security code for at least one security imprint, thereby producing a recalculated security code, and to initiate an accounting operation for said monetary value and to communicate the recalculated security code to said separate data processing unit.

and to immediately communicate said next-successive data authorization code to said separate data processing unit.

6. An arrangement as claimed in claim 3 wherein said internal non-volatile memory is an SRAM of said processor, and wherein said security module further comprises a battery supporting said SRAM, and wherein said SRAM had memory areas for protected storage of at least some data produced by said pre-calculation, and wherein said at least one key for calculating said data authorization code is protectively stored in a memory area of said SRAM.

7. An arrangement as claimed in claim 6 wherein said processor is programmed by said first program to calculate said data authorization code using a machine identifier and OCR key indicator, a date, said monetary value, and a register value for an ascending register.

8. An arrangement as claimed in claim 2 wherein said processor is programmed by said first memory to calculate said data authorization code using an algorithm selected from the group consisting of DES algorithms and triplet DES algorithms.

9. A method for generating a security imprint, comprising the steps of:
providing a security module containing a security module data processing unit;
presetting all system data required for calculating a security code and, upon receipt of new system data requiring a re-calculation of the security code, in said security module data processing unit immediately validating said new system data and re-calculating said security code using said new system data;

also in said security module data processing unit calculating an ascending register value for a monetary value associated with said new system data; and

communicating the re-calculated security code to a separate data processing unit external of said security module and compiling a print image, including said security code as a security imprint and printing said print image.

10. A method as claimed in claim 9 comprising calculating a data authorization code in said security module data processing unit as said security code dependent on said ascending register value and additional data in said new system data and generating said security imprint at a time following an end of entry of said new system data and before conducting an accounting for said monetary value.

11. A method as claimed in claim 9 wherein said new system data are associated with an inserted mail item and wherein said security code is a data authorization code and wherein said security module data processing unit calculates said data authorization code dependent on said ascending register value and additional data in said new system data at a time from said insertion of said mail item and before conducting an accounting for said monetary value.

12. A method as claimed in claim 9 wherein said security code is a data authorization code and wherein said security module data processing unit calculates said data authorization code dependent on a machine identifier, said monetary value and a current date, and wherein at least said machine identifier is included in a pre-calculation of n bytes of said data authorization code.

13. A method as claimed in claim 9 wherein said security code is a data authorization code and wherein said security module data processing unit calculates said data authorization code dependent on a machine identifier, said monetary value and a current date, and wherein at least said machine identifier and said date is included in a pre-calculation of n bytes of said data authorization code.

14. A method as claimed in claim 9 comprising successively supplying sets of new system data to said security module data processing unit and after communicating said security code to said separate data processing unit, in said security module data processing unit beginning calculation of a next-successive security code for next new system data, at least dependent on said ascending register value to produce pre-calculated n bytes of said next-successive security code.

004730" 904E6560